



SD49707

| SYM | REVISION DESCRIPTION | DFTM | DATE | APPD | DATE |
|-----|-------------------------|----------|----------|----------|--------|
| A | RELEASED FOR PRODUCTION | M. J. R. | 3/24/04 | J. D. B. | 4/7/04 |
| B | CHANGED PER CDC #23695 | M. J. R. | 4/27/04 | J. D. B. | 8/2/04 |
| C | CHANGED PER CDC #24271 | D. J. H. | 12/23/04 | J. D. B. | 1/5/05 |



MARKING VIEW "B"



5/16-24 UNF-2A
1/4 HEX. SOC.

MARKING VIEW "A"

NOTES:

- O-RING P/N: MIL-R-25988/1-140
- MOUNTING BOLT TO BE TORQUED TO 50-100 IN-LBS.

NOTICE OF PROPRIETARY RIGHTS
THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA, INCLUDING TRADE SECRETS, PROPRIETARY TO TIMES MICROWAVE SYSTEMS. DISCLOSURE OF THIS DATA IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WITHIN YOUR COMPANY ONLY. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF TIMES MICROWAVE SYSTEMS.

| | | |
|-----------|--------------------|---------|
| DRAFTSMAN | M. Rockett | 3/24/04 |
| CHECKER | John D. Bloomfield | 4/7/04 |
| APPROVED | John D. Bloomfield | 4/7/04 |

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN INCHES
MACHINED SURFACES FINISH N/A RMS MAX.
REMOVE ALL BURRS .005 MAX. BREAK
MACHINE CORNERS .005 MAX. FILLET R.
TOLERANCES ON DECIMALS
.XX ± .03 .XXX ± .005
ANGLES ± 1° FRACTIONS ± 1/32

DO NOT SCALE DRAWING

| | | |
|--|----------|---------------|
| TIMES MICROWAVE SYSTEMS | | |
| TITLE: PLUG, RECTANGULAR FOR 12 TMS M8 PLUG COAXIAL CONTACTS (.440 SPACING) | | |
| DWG. SIZE | B | REV. C |
| DRWG. NO. | SD49707 | |
| CODE IDENT. | 68999 | |
| SCALE | NONE | SHEET: 1 of 1 |

MATERIAL:
ALUMINUM ALLOY, 6061-T6511
PER QQ-A-200/8 OR QQ-A-225/8

FINISH: ELECTROLESS NICKEL PLATE PER
SAE-AMS-C-26074 CLASS 1, THEN CADMIUM PLATE PER
SAE-AMS-QQ-P-416, TYPE II

012320
W.O. NUMBER