

Standard Ground Kits




Pre-formed copper strap facilitates easy installation and protects coax from lightning strikes in excess of 200 kA

Application: Grounding
 Size: Versions for coax and elliptical waveguide
 Design: Bolt-on style with 5' (1.6m) lead / crimp lug
 Feature: RoHS compliant
 Mounts to: Coax outer conductor
 Material: Tin plated copper strap
 Includes: Ground kit, lug, weatherproofing kit
 Order Sep.: —

| | TMS part no. | Quant/pkg. | Weight lb | (kg) |
|--|--------------|------------|-----------|-------|
| Standard Ground Kit for LMR-195 Coaxial Cable | GK-S195TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-200 Coaxial Cable | GK-S200TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-240 Coaxial Cable | GK-S240TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-300 Coaxial Cable | GK-S300TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-400 Coaxial Cable | GK-S400TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-500 Coaxial Cable | GK-S500TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-600 Coaxial Cable | GK-S600TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-900 Coaxial Cable | GK-S900TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-1200 Coaxial Cable | GK-S1200TT | 1 | 1.4 | (0.6) |
| Standard Ground Kit for LMR-1700 Coaxial Cable | GK-S1700TT | 1 | 1.4 | (0.6) |

4" Feed-thru Entry Panels



Traditional panel for weather-tight building penetration

Application: Entry Port Solutions
 Size: 20 configurations
 Design: Entry plates with round ports
 Feature: Easy to install solution
 Mounts to: Walls
 Material: Aluminum
 Includes: Port, caps, mounting hardware
 Order Sep.: 4" (101.6mm) Boot Assemblies

| | TMS part no. | Quant/pkg. | Weight lb | (kg) |
|---------------------------------------|--------------|------------|-----------|-------|
| Entry Panel, 1 port, 1 x 1, standard | EP-220 | 1 | 1.0 | (0.5) |
| Entry Panel, 1 port, 1 x 1, compact | EP-574 | 1 | 0.6 | (0.3) |
| Entry Panel, 2 port, 1 x 2 | EP-1448 | 1 | 2.3 | (1.0) |
| Entry Panel, 3 port, 1 x 3 | EP-1635 | 1 | 2.9 | (1.3) |
| Entry Panel, 4 port, 1 x 4 | EP-575 | 1 | 3.5 | (1.6) |
| Entry Panel, 4 port, 2 x 2, standard | EP-1199 | 1 | 4.2 | (1.9) |
| Entry Panel, 4 port, 2 x 2, compact | EP-1650 | 1 | 4.0 | (1.8) |
| Entry Panel, 6 port, 2 x 3 | EP-1449 | 1 | 6.1 | (2.8) |
| Entry Panel, 6 port, 1 x 6 | EP-1477 | 1 | 6.0 | (2.7) |
| Entry Panel, 8 port, 2 x 4, standard | EP-576 | 1 | 6.1 | (2.8) |
| Entry Panel, 8 port, 2 x 4, large | EP-1338 | 1 | 6.0 | (2.7) |
| Entry Panel, 9 port, 3 x 3 | EP-1033 | 1 | 7.1 | (3.2) |
| Entry Panel, 10 port, 2 x 5 | EP-1297 | 1 | 7.4 | (3.4) |
| Entry Panel, 12 port, 3 x 4, standard | EP-1118 | 1 | 8.5 | (3.9) |
| Entry Panel, 12 port, 3 x 4, large | EP-1334 | 1 | 7.0 | (3.2) |
| Entry Panel, 12 port, 2 x 6 | EP-1336 | 1 | 9.2 | (4.2) |
| Entry Panel, 16 port, 4 x 4 | EP-1447 | 1 | 9.1 | (4.1) |
| Entry Panel, 18 port, 3 x 6 | EP-1333 | 1 | 13.0 | (5.9) |
| Entry Panel, 20 port, 4 x 5 | EP-1861 | 1 | 11.0 | (5.0) |
| Entry Panel, 24 port, 4 x 6 | EP-1340 | 1 | 15.8 | (7.2) |

Note: Custom configurations available. Contact your sales administrator for details