Data Sheet

Within Series Adaptor 37_BNC-50-0-2/133_N



Description

Panel adaptor jack/jack, flange mount BNC jack (female) / BNC jack (female)

Interface standard
Series BNC - IEC 61169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

 $\begin{array}{ll} \mbox{Impedance} & 50 \ \Omega \\ \mbox{Interface frequency max.} & 4 \ \mbox{GHz} \\ \mbox{VSWR} & DC - 4 \ \mbox{GHz} \\ \mbox{\leq 1.06 + 0.04 f (GHz)$} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0134 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Interface - BNC jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Interface - BNC jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing DCA-00013596
Mounting hole DOU-00009005

Ordering Information

 Single package
 37_BNC-50-0-2/133_NE

 Bulk 100 pcs package
 37_BNC-50-0-2/133_NH

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.