

## Between Series Adaptor 33\_N-BNC-50-51/1--\_U

### Description

Adaptor plug/jack  
N-precision plug (male) / BNC-precision jack (female)

For Test & Measurement applications  
Precision adaptor

Interface standards  
Series N-precision - IEC 60169-16\_MIL-STD-348A/402\_CECC 22210  
Series BNC-precision - IEC 60169-8\_MIL-STD-348A/404\_CECC 22120



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
VSWR	DC - 4 GHz ≤ 1.05 + 0.01 f (GHz)

#### Mechanical Data

Number of matings	500
Weight	0.0438 kg

#### Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EC (RoHS)	compliant

#### Material Data

Interface - N-precision plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - BNC-precision jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

### Related Documents

Catalogue drawing	DCA-00014328
-------------------	--------------

### Ordering Information

Single package	33_N-BNC-50-51/1--_UE
----------------	-----------------------

### Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C