

AD-H3H3	MHV Plug To MHV Plug		50Ω																								
<p>Technical drawing of the AD-H3H3 MHV Plug To MHV Plug coupler. The drawing shows a side view of the device with dimensions: diameter is <math>\phi 14.5</math> (0.571) and length is 35 (1.378).</p>																											
<p>VSWR 1.20 : 1 MAX UP TO 0.3 GHz</p>																											
<table border="1"> <thead> <tr> <th>Parts</th> <th>Material</th> <th>Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Body</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Contact Pin</td> <td>Brass</td> <td>Gold 5 Over Nickel 50 Over Copper 50</td> </tr> <tr> <td>Gasket</td> <td>Silicon</td> <td></td> </tr> <tr> <td>Spring</td> <td>Sk5</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Washer</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Coupling Nut</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> </tbody> </table>	Parts	Material	Plating (Micro-inch)	Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Contact Pin	Brass	Gold 5 Over Nickel 50 Over Copper 50	Gasket	Silicon		Spring	Sk5	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Washer	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Insulator	Teflon		Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50			
Parts	Material	Plating (Micro-inch)																									
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																									
Contact Pin	Brass	Gold 5 Over Nickel 50 Over Copper 50																									
Gasket	Silicon																										
Spring	Sk5	Tin-Zinc-Copper-Alloy 100 Over Copper 50																									
Washer	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																									
Insulator	Teflon																										
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																									
<p>Weight: 19.15 g</p>																											

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.