Data Sheet



Within Series Adaptor 32_N-75-0-1/133_N

Description

Adaptor plug/plug N plug (male) / N plug (male)

Interface standard
Series N - Not compatible to N 50 Ohms



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 75 \ \Omega \\ \text{Interface frequency max.} & 1.5 \ \text{GHz} \end{array}$

Mechanical Data

Number of matings 500
Weight 0.0533 kg

Environmental Data

Operating temperature -65 °C to 165 °C 2011/65/EU (RoHS) compliant

Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Catalogue drawing DCA-00013682

Ordering Information

Single package 32_N-75-0-1/133_NE

Data Sheet

Within Series Adaptor 32_N-75-0-1/133_N



HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.