

Between Series Adaptor 32_N-TNC-50-1/---_U

Description

Adaptor plug/plug
N plug (male) / TNC plug (male)



Interface standards
Series N - IEC 61169-16_MIL-STD-348A/304_CECC 22210
Series TNC - IEC 60169-17_MIL-STD-348A/313_CECC 22200

Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz
VSWR DC - 11 GHz
≤ 1.06 + 0.11 f (GHz)

Mechanical Data

Number of matings 500
Weight 0.0451 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU (RoHS) compliant

Material Data

Interface - N plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Interface - TNC plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (without Nickel underplating)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Catalogue drawing DCA-00014465

Ordering Information

Single package 32_N-TNC-50-1/---_UE