

## Within Series Adaptor 34\_N-50-0-51/193\_N

### Description

Bulkhead adaptor jack/jack  
N-precision jack (female) / N-precision jack (female)

For Test & Measurement applications  
Precision adaptor

Interface standard  
Series N-precision - IEC 60169-16\_MIL-STD-348A/402\_CECC 22210



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz
VSWR	DC - 18 GHz ≤ 1.03 + 0.01 f (GHz)
Electrical length	27.39 mm

#### Mechanical Data

Number of matings	500
Weight	0.0508 kg

#### Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EC (RoHS)	compliant

#### Material Data

Interface - N-precision jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Gasket	VMQ (Silicone rubber)	

Interface - N-precision jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	
Gasket	VMQ (Silicone rubber)	

### Related Documents

Outline drawing	DOU-00013622
-----------------	--------------

### Ordering Information

Single package	34_N-50-0-51/193_NE
----------------	---------------------

### Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C

## Within Series Adaptor 34\_N-50-0-51/193\_N