



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. STAINLESS STEEL PER QQ-S-764
 2. PASSIVATE PER QQ-P-35
 3. BERYLLIUM COPPER PER QQ-C-530
 4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-1946B

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	DRAWING NO.	SCALE	5/1	ISSUE	A	FILE NO.	F:\DWG\SMA\2071A1\002\50\SPTS0GSZ
6	GASKET	SILICONE	RED	2	GS-6/43X06						
5	RETAINER RING	NOTE 3	NATURAL	2	SMA5000-4-B						
4	CONTACT PIN	NOTE 3	NOTE 4	1	CP11AKJ01A						
3	INSULATOR	NOTE 5	NATURAL	2	SMA5900-3T-50-A						
2	BODY	NOTE 1	NOTE 2	1	SMA5900-2-A						
1	SHELL	NOTE 1	NOTE 2	2	SMA5000-1-C						

DIMENSIONS ARE IN MILLIMETERS		PART NO. 13216883-10A	Amphenol Danbury,CT,USA-Tainan,Taiwan-Shenzhen,China
UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVED <i>Chakof</i> DATE	
0.5-6 = ±0.2		CHECKED <i>Joslen</i> DATE 09-04-04'	
6-30 = ±0.4		DRAWN <i>Derrillo</i> DATE 09-04-04'	
30-120 = ±0.6			TITLE SMA PLUG ADAPTOR
120-315 = ±1			DRAWING NO. SMA2071A1-002-S/PT50G-50
315-1000 = ±1.6			ITEM NO. 112071AAD00PA5F
1000-2000 = ±2.4			