

Within Series Adaptor 33_PC185-50-0-1/199_NE

Description

Adaptor plug/jack
PC 1.85 plug (male) / PC 1.85 jack (female)

For Test & Measurement applications
Precision adaptor

Interface standard
Series PC 1.85 - IEC 60169-32



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	65 GHz		
Frequency range	DC to 25 GHz	25 to 45 GHz	45 to 65 GHz
Return loss	≥ 31.9 dB	≥ 30 dB	≥ 26 dB

Mechanical Data

Number of matings	500
Weight	0.0056 kg

Environmental Data

Operating temperature	-55 °C to 155 °C
2011/65/EC (RoHS)	compliant

Material Data

Interface - PC 1.85 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	
Coupling nut	Stainless Steel	Passivated (Plating)

Interface - PC 1.85 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)
Insulator	LCP (Liquid crystal polymer)	

Related Documents

Outline drawing	DOU-00282086
-----------------	--------------

Ordering Information

Single package	33_PC18-50-0-1/199NE
----------------	----------------------