



HOUSING: STEEL, CRES ALLOY UNS-S30300
PER ASTM-A582.
PASSIVATE PER QQ-P-35.

COUPLING NUT: STEEL, CRES ALLOY UNS-S30300
PER ASTM-A582.
PASSIVATE PER QQ-P-35.

CONTACT: BeCu
UNS-C17300 PER ASTM-B-196/197.
GOLD PLATE PER MIL-G-45204.

DIELECTRIC: ULTEM 1000 PER ASTM-D-5205.

DIELECTRIC: KEL-F PER MIL-P-46036.

RETAINING RING: BeCu
UNS-C17300 PER ASTM-B-196/197.

GASKET: SILICONE RUBBER PER ZZ-R-765.

MATERIAL & FINISH

CONTACT GAGING SPEC.	91P52118
SPECIFICATIONS	91P56681
INTERFACE-2.40 PLUG	91P53660
INTERFACE-3.5 JACK	91F52012
SPECIFICATION GROUP	DRAWING NO.

A		RELEASE	11/17/00	DWDC
REV.	ECN	DESCRIPTION	DATE	APPVD

DRAWN	EJO	DATE	6/20/00	APRVD.	DWDC	DATE	11/14/00
-------	-----	------	---------	--------	------	------	----------

TITLE	61420-00SF 2.40mm PLUG TO 3.5mm JACK ADAPTER
-------	--



Southwest Microwave, Inc.
9055 South McKemy Street
Tempe, Arizona 85284-2946
Telephone (480) 783-0201
Fax (480) 783-0360

SCALE	3:1	DWG. NO.	79Y56428	REV.	A
SHEET	1 OF 1				