

5. VSWR NOT TO EXCEED 1.3:1 THRU 18 GHz 4. ADAPTER TO MEET OR EXCEED ALL

- SPECIFICATIONS PER MIL-39012
- 3. FINISH:
- BODY AND COUPLING NUT: PASSIVATE PER QQ-P-35 CONTACT: GOLD PER MIL-G-45204: TYPE II, CLASS 2, OVER COPPER PER MIL-C-14550, CLASS 4
- 2. MATERIAL:
 - BODY: STAINLESS STL PER QQ-S-764 TYPE 303 COUPLING NUT STAINLESS STL PER QQ-S-764 TYPE 303 CONTACT: BERYL. COPPER PER QQ-C-530 INSULATOR: TEFLON PER MIL-P-19468A
- 1. MATING DIMS IN ACCORDANCE WITH MIL-STD-348

NOTES :

NOTICE This drawing embodies a CONFIDENTIAL proprietary design originated by United Microwave Products, Inc., and all design, manufacturing, reproduction, use and sale rights regarding the same are expressly reserved. It is submitted under a confidential relationship for a specified purpose and the recipient agrees by accepting this drawing not to supply or disclose any information regarding it to any unauthorized person or to incorporate in other projects any special feature peculiar to this design. All patent rights hereto are expressly reserved by United Microwave Products Inc.		TOLERANCES AND NOTES EXCEPT AS NOTED DIMENSIONS ARE IN INCHES LINEAR XX ± .030 ANGULAR ± 1/2 ° FRACTION ± 1/32 XXX ± .010 1. MACHINE FINISH 3. ALL MACHINED FILLETS 4. ALL MACHINED FILLETS 4. ALL MACHINED DIAMETERS TO BE. CONCENTRIC WITHIN .002003 T.I.R. 6. DIMENSIONS TO BE MET BEFORE PLATING. 7. CHAMPER ALL THOS .45 DEGREES		MATERIAL	SIZE	SPECIFIC	CATION	PROCUREMENT	
					-	•	APPR. ENG.		
			UNITED MICROWAVE PRODUCTS Inc.			CHK. DR.			
WEIGHT N/A	NONE	9. REMOVE FRAYED EDGES ON TEFLON. 10. REMOVE ALL BURRS.	SMA PLUG to SMA JACK SWEEP RIGHT ANGLE 18 GHz				370-SF		