



- 6. 9/16 HEX OPTIONAL FOR TNC COUPLING NUT
- 5. VSWR NOT TO EXCEED 1.20:1 FROM DC TO 11 GHz & 1.30:1 FROM 11GHz TO 18 GHz
- 4. ADAPTOR TO MEET OR EXCEED ALL SPECIFICATIONS PER MIL-39012
- 3. FINISH:
 - BODY AND COUPLING NUT: PASSIVATE PER QQ-P-35
 - CONTACT: GOLD PER MIL-G-45204; TYPE II,
 - CLASS 2, OVER COPPER PER MIL-C-14550, CLASS 4
- 2. MATERIAL:
 - BODY: STAINLESS STL PER QQ-S-764 TYPE 303
 - COUPLING NUT STAINLESS STL PER QQ-S-764 TYPE 303
 - CONTACT: BERYL. COPPER PER QQ-C-530
 - INSULATOR: TEFLON PER MIL-P-19468A
- 1. MATING DIMS IN ACCORDANCE WITH MIL-STD-348

NOTES :

PART NO.	1-9	10-24	25-49	50-99	100+
1820	\$37.50	\$36.50	\$34.50	\$33.00	\$31.00

<p>NOTICE</p> <p>This drawing embodies a CONFIDENTIAL, proprietary design originated by United Microwave Products, Inc., and all design, manufacturing, reproduction, use and sale rights regarding the same are expressly reserved. It is submitted under a confidential relationship for a specified purpose and the recipient agrees by accepting this drawing not to supply or disclose any information regarding it to any unauthorized person or to incorporate in other projects any special feature peculiar to this design. All patent rights hereto are expressly reserved by United Microwave Products Inc.</p>	<p>TOLERANCES AND NOTES EXCEPT AS NOTED DIMENSIONS ARE IN INCHES</p> <p>LINEAR .XX ± .015 ANGULAR ± 1/2 ° FRACTION ± 1/32 XXX ± .005</p> <p>1. MACHINE FINISH $\sqrt{32}$ RMS</p> <p>2. BREAK ALL SHARP EDGES .002</p> <p>3. ALL MACHINED FILLETS</p> <p>4. ALL MACHINED SURFACES SQUARE TO RESPECTIVE AXIS WITHIN .003 PER INCH.</p> <p>5. MACHINED DIAMETERS TO BE CONCENTRIC WITHIN .002 - .003 T.I.R.</p> <p>6. DIMENSIONS TO BE MET BEFORE PLATING.</p> <p>7. CHAMFER ALL THDS 45 DEGREES</p> <p>8. THREADS PER H-2B</p> <p>9. REMOVE FRAYED EDGES ON TEFLON.</p> <p>10. REMOVE ALL BURRS.</p>		<p>UNITED MICROWAVE PRODUCTS Inc.</p> <p>TNC PLUG TO TNC JACK</p>		1820-SF
	<p>WEIGHT</p> <p>N/A</p>	<p>SCALE</p> <p>NONE</p>	<p>MATERIAL</p>	<p>SIZE</p>	<p>SPECIFICATION</p>