

**1671J Coax - 50 Ohm Microwave Cable**

 	<p>For more information please call <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
--	---

**Description:**

RG-405/U type, 24 AWG solid .020" silver-plated copper-covered steel conductor, TFE Teflon® insulation, copper-tin composite shield (100% coverage), PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Coax	1
Total Number of Conductors	1
RG Type	405/U
AWG	24
Stranding	Solid
Conductor Diameter	.020 in.
Conductor Material	SPCCS - Silver Plated Copper Covered Steel

**INSULATION:**

Insulation Material Trade Name	Teflon®
Insulation Material	TFE - Tetrafluoroethylene
Insulation Diameter	.062 in.

**OUTER SHIELD:**

Outer Shield Type	Tape/Braid
-------------------	------------

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1		Tape	Copper Foil	100
2		Braid	Tin-Filled Composite	100

Outer Shield % Coverage	100 %
-------------------------	-------

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.127 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-40°C To +105°C
UL Temperature Rating	105°C (UL AWM Style 10245)

**1671J Coax - 50 Ohm Microwave Cable**

Non-UL Temperature Rating	105°C
Bulk Cable Weight	16 lbs/1000 ft.
Max. Recommended Pulling Tension	26 lbs.
Min. Bend Radius (Install)	0.12 in.
Min. Bend Radius (Continuous Flexing)	0.37 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

AWM Specification	UL Style 10245 (30 V 105°C)
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2005

**FLAME TEST:**

Other Flame Test	Horizontal Wire
------------------	-----------------

**SUITABILITY:**

Suitability - Indoor	Yes
Suitability - Outdoor	Yes

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
--------------	---

**ELECTRICAL CHARACTERISTICS:**

Nom. Characteristic Impedance	50 Ohms
Nom. Inductance	.07 µH/ft
Nom. Capacitance Conductor to Shield	29.5 pF/ft
Nominal Velocity of Propagation	69.5 %
Nominal Delay	1.46 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	64.2 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	10.2 Ohms/1000 ft

**Maximum VSWR :**

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Maximum VSWR
	500			1.1:1
	20000			1.3:1

Nom. Attenuation :

**1671J Coax - 50 Ohm Microwave Cable**

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	500			15.0
	1000			22.2
	2000			32.8
	3000			41.2
	5000			54.9
	7000			66.4
	10000			81.2
	15000			102
	18000			113
	20000			120

Max. Power Rating :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Power Rating (W)
	500			180
	1000			119
	2000			79
	3000			62
	5000			46
	7000			37
	10000			30
	15000			24
	18000			21
	20000			20

Max. Operating Voltage - UL 30 V RMS (UL AWM Style 10245)

Max. Operating Voltage - Non-UL 1500 V RMS

**NOTES:**

Notes US Patents 4, 694, 122 & 5, 293, 001. Patent held in the U.S., Singapore, Australia, Germany, France, and England. Patent pending in Japan. Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1671J 010100	#24 TFE BRD TINNED COAX PVC	100	2.4	BLACK	
1671J 0101000	#24 TFE BRD TINNED COAX PVC	1000	17	BLACK	V
1671J 010500	#24 TFE BRD TINNED COAX PVC	500	9.5	BLACK	V

V = 250' PUT-UP EXACT LENGTH MAXIMUM OF 3 PIECES MINIMUM LENGTH 50' 500' PUT-UP EXACT LENGTH MAXIMUM OF 5 PIECES MINIMUM LENGTH 50' 1000' PUT-UP EXACT LENGTH MAXIMUM OF 8 PIECES MINIMUM LENGTH 50'

Revision Number: 3 Revision Date: 10-03-2005

---

## 1671J Coax - 50 Ohm Microwave Cable

---

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.