

Coaxial PCB Connector 82_MMCX-50-0-8/111_O

Description

Straight PCB jack

Interface Standards
SUHNER-MMCX



Technical Data

Electrical Data

Impedance
Interface frequency max.

50 Ω
6 GHz

Mechanical Data

Board mounting type
Weight

surface mount
0.0003 kg

Environmental Data

Operating temperature
2011/65/EU (RoHS - including
2015/863 and 2017/2102)

-55 °C to 155 °C
compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Outline drawing
Catalogue drawing
Mounting hole

DOU-00012947
DCA-00012949
DCA-00085694

Ordering Information

Tape and Reel package
Single package

82_MMCX-50-0-8/111_OM
82_MMCX-50-0-8/111_OE

Remarks

PCB connector without stand-offs

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)
[82_MMCX-50-0-8/111_OE](#)