

Coaxial Cable Connector 25_BMA-50-2-2/119_N

Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-33_MIL-STD-348A/321



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	18 GHz

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0055 kg

Environmental Data

Operating temperature 2011/65/EC, RoHS	-65 °C to 125 °C compliant
---	-------------------------------

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Other body part	Stainless Steel	
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing	DCA-00008815
Assembly instruction	DOC-0000180997
Mounting hole	DOU-00008816

Ordering Information

Single package	25_BMA-50-2-2/119_NE
Bulk 100 pcs package	25_BMA-50-2-2/119_NH

Additional Information

Suitable cables	EZ_86_TP_M17
-----------------	--------------