## **Data Sheet**

## Coaxial Panel Connector 22\_BNC-50-0-16/133\_N

## **Description**

Straight bulkhead receptacle jack

Interface standards IEC 60169-8\_MIL-STD-348A/301\_CECC 22120

## **Technical Data**

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	4 GHz	
Mechanical Data		
Number of matings	500	
Weight	0.0102 kg	
Environmental Data		
Operating temperature	-65 °C to 165 °C	
2011/65/EU (RoHS)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Related Documents		
Outline drawing	DOU-00011424	
Catalogue drawing	DCA-00011426	
Mounting hole	DOU-00008762	
Ordering Information		

Single package

22\_BNC-50-0-16/133\_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.



