

Coaxial Cable Connector 24_BNC-50-3-33/133_N

Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-8_MIL-STD-348A/301_CECC 22120



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0167 kg

Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU, RoHS	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Related Documents

Outline drawing	DOU-00009980
Catalogue drawing	DCA-00009846
Assembly instruction	DOC-0000179121
Mounting hole	DOU-00008751

Ordering Information

Single package	24_BNC-50-3-33/133_NE
Bulk 100 pcs package	24_BNC-50-3-33/133_NH

Additional Information

Suitable cables	EZ_141_TP_M17
-----------------	---------------