

DATE REVISED: 3/13/98

| CATALOG NUMBER | "L" LENGTH | CONTACT END | |
|-------------------|------------|-------------|--|
| A007-L45-02-TAB-R | SEE CHART | RADIUS-R | |
| A007-L45-02-TAB-S | SEE CHART | SQUARE-S | |

TAB EQUALS "L" X 10⁴ IN.

| LENGTH CHART |
|--------------|
| .030 |
| .035 |
| .040 |
| .045 |
| .050 |
| .055 |
| .060 |
| .065 |
| .070 |
| .075 |
| .080 |
| .085 |
| .090 |
| .095 |
| .100 |
| .105 |
| .110 |
| .115 |
| .120 |
| .125 |
| .130 |
| .135 |
| .145 |

HOUSING AND CENTER CONTACT: IRON-NICKEL-COBALT SEALING ALLOY (KOVAR) PER ASTM F 15; GOLD PLATE

DIELECTRIC: CORNING 7070 GLASS

RECOMMENDED MOUNTING HOLE

This drawing and any data contained herein is the property of Corning Gilbert Inc., and constitutes and contains proprietary and confidential information. Neither receipt nor possession of this drawing confers or transfers any right to duplicate, use or disclose any information contained herein except as expressly authorized by Corning Gilbert Inc.

| | | |
|--|----------------------|-----------------------------|
| GPO MALE SMOOTH BORE SOLDER-IN HERMETIC SHROUD | IDENT CODE: 82316 | Corning Gilbert Inc. |
| | REVISION: K | |

| | | | |
|-------------------------|------------------------------|----------------|--|
| SOURCE FILE: MECR# 2775 | DWG. NO.: OL-A007-L45-02-TAB | ASSY. PROC.: — | |
|-------------------------|------------------------------|----------------|--|