

Coaxial Cable Connector 11_H4-50-3-1/133_N

Description

Straight cable plug

Interface standards



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 0.3 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | clamped |
| Weight | 0.0228 kg |

Environmental Data

| | |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU, RoHS | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|-----------------------|-----------------------------------|
| Centre contact | Brass | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Coupling nut | Brass | SUCOPLATE (R) Plating |
| Gasket | VMQ (Silicone rubber) | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00071792 |
| Catalogue drawing | DOU-00005810 |
| Assembly instruction | DOC-0000179536 |

Ordering Information

| | |
|----------------|---------------------|
| Single package | 11_H4-50-3-1/133_NE |
|----------------|---------------------|

Additional Information

| | |
|-----------------|------------------------------|
| Suitable cables | RG_58_C/U, G_03232, GX_03272 |
|-----------------|------------------------------|