Data Sheet

Coaxial PCB Connector 82_MCX-S50-0-29/111_N

Description

Straight PCB jack

Interface Standards IEC 60169-36_CECC 22220





Technical Data

Electrical Data Impedance Interface frequency max.	50 Ω 6 GHz	
Mechanical Data		
Board mounting type Weight	surface mount 0.0004 kg	
Environmental Data		
Operating temperature 2011/65/EU (RoHS)	-55 °C to 155 °C compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPRO Plating
		SUCOPRO Plating
Body	Brass	SUCUFRU Flating

ocuments

DOU-00012753
DCA-00012755
DOU-00012756

Ordering Information

Bulk 100 pcs package	82_MCX-S50-0-29/111_NH
Tape and Reel package	82_MCX-S50-0-29/111_NM
Single package	82_MCX-S50-0-29/111_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.