


NOTES:

1. SPECIFICATIONS PER IDS-168.
2. ACCOMMODATES RG-316 OR EQUIVALENT CABLES.
3. DESIGNED FOR USE IN ARINC HOUSINGS, SIZE 12 CAVITY.
4. BULLET AND SPACER SUPPLIED LOOSE.
5. FREQUENCY: DC TO 3 GHZ.



WARNING - THIS DOCUMENT CONTAINS TECHNICAL DATA WHOSE EXPORT IS RESTRICTED BY THE ARMS EXPORT CONTROL ACT (TITLE 22, U.S.C., SEC 2751, ET. SEQ.) OR THE EXPORT ADMINISTRATION ACT OF 1979, AS AMENDED, TITLE 50, U.S.C., APP 2401 ET SEQ. VIOLATIONS OF THESE EXPORT LAWS ARE SUBJECT TO SEVERE CRIMINAL PENALTIES. DISSEMINATE IN ACCORDANCE WITH PROVISIONS OF DOD DIRECTIVE 5230.25.											
MATERIAL:				UNLESS OTHERWISE SPECIFIED, PHOENIX WORKMANSHIP STANDARDS APPLY. DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS.		APPROVALS DRAWN SST 05/03/19 CHECKED JEM 05/03/19 QA MFG ENGINEER SST 05/03/19 APPROVED JEM 05/03/19		DATE 05/03/19 05/03/19		The PHOENIX Company of Chicago™ 22 GREAT HILL RD., NAUGATUCK, CT 06770 WWW.PHOENIXOFCHICAGO.COM	
TOLERANCES ARE: FRACTIONS: ± 1/64 DECIMALS: .XX ± .01 .XXX ± .003 ANGLES: ± 1/2°				32		TITLE SIZE 12 PKZ RECEPTACLE DIRECT SOLDER		SIZE A FSCM 58167 DWG NO 168-1020-0670 SCALE		REV C PLATING OPT. A,C SHEET 1 OF 1	
REV.	DESCRIPTION	DATE	APPR.	THE INFORMATION DISCLOSED IN THIS DOCUMENT IS CONFIDENTIAL AND PROPRIETARY TO PHOENIX CO. INC. AND MAY NOT BE USED FOR MANUFACTURE OR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF THE PHOENIX CO. OF CHICAGO INC.		F.S.R. #		SHEET 1 OF 1		F.S.R. #	
C	PER ECN 13309	5/3/2019	JEM								
B	PER ECN 13163	10/26/2018	JEM								
A	REL. PER ECN 12554	7/11/2017	RMB								