

## Coaxial Cable Connector 21\_MMPX-50-2-1/111\_N

### Description

Straight cable jack

Interface standards

HUBER+SUHNER MMPX STD (Patent US 7.294.023)



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$		
Interface frequency max.	67 GHz		
Frequency range	DC to 26.5 GHz	26.5 to 50 GHz	50 to 67 GHz
Return loss	25 dB	20 dB	20 dB

#### Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0003 kg

#### Environmental Data

Operating temperature	-65 °C to 155 °C
2011/65/EU, RoHS	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	SUCOPRO / Gold Plating
Outer contact	Copper Beryllium Alloy	SUCOPRO / Gold Plating
Body	Brass	SUCOPRO / Gold Plating

### Related Documents

Outline drawing	DOU-00056827
Catalogue drawing	DCA-00087893
Assembly instruction	DOC-0000236433

### Ordering Information

Single package	21_MMPX-50-2-1/111_NE
----------------	-----------------------

### Additional Information

Suitable cables	EZ_86_TP_M17, EZ_86_AL_TP_M17, SUCOFORM_86, STORM_SR_86
-----------------	---

### Remarks

Decoupling tool MMPX shall be used (74\_Z-0-0-491/74\_Z-0-0-555)!