

Coaxial Cable Connector 16_MMPX-50-2-2/111_N

Description

Right angle cable plug

Interface standards

HUBER+SUHNER MMPX STD (Patent US 7.294.023)



Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	67 GHz		
Frequency range	DC to 26.5 GHz	26.5 to 50 GHz	50 to 67 GHz
Return loss	25 dB	20 dB	20 dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.000359 kg

Environmental Data

Operating temperature 2011/65/EU, RoHS	-65 °C to 155 °C compliant
-------------------------------------------	-------------------------------

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PTFE (Polytetrafluoroethylene)	

Related Documents

Outline drawing	DOU-00119847
Catalogue drawing	DCA-00087892
Assembly instruction	DOC-0000273989

Ordering Information

Single package	16_MMPX-50-2-2/111_NE
Reuseable package	16_MMPX-50-2-2/111_NI

Additional Information

Suitable cables	MULTIFLEX_86
-----------------	--------------

Remarks

Decoupling tool MMPX shall be used (74_Z-0-0-491/74_Z-0-0-555)!