

## Coaxial Cable Connector 11\_N-50-3-5/133\_N

### Description

Straight cable plug

Interface standards

IEC 61169-16\_MIL-STD-348A/304\_CECC 22210



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 11 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact clamped  
Weight 0.0365 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU (RoHS - including  
2015/863 and 2017/2102) compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

### Related Documents

Outline drawing DOU-00008106  
Catalogue drawing DOU-00006125  
Assembly instruction DOC-0000177464

### Ordering Information

Bulk 100 pcs package 11\_N-50-3-5/133\_NH  
Single package 11\_N-50-3-5/133\_NE

### Additional Information

Suitable cables RADOX\_RF\_400, ENVIROFLEX\_142, RG\_400\_U, RG\_223\_U, RG\_142\_B/U