



NOTES:

1. DESIGN AND INTERFACE PER I. D. S. -78.
2. DESIGN TO FIT MIL-C-38999, SERIES I, III & IV HOUSINGS.
3. 50 Ohm LOAD. POWER - 0.5 WATT AT AMBIENT TEMPERATURE 30°C (86°F), DERATED LINEARLY TO ZERO WATT AT 130°C (266°F) AMBIENT TEMPERATURE.
4. RETURN LOSS NOT LESS THAN 22 dB FROM 100 MHz TO 6.5 GHz.

SHEET 1 OF 2

				<p>PALCO CONNECTOR</p> <p>22 GREAT HILL RD., NAUGATUCK, CT 06770</p> <p>UNLESS OTHERWISE SPECIFIED, PALCO WORKMANSHIP STANDARDS APPLY</p> <p>TOLERANCES ON DECIMALS: XX ±.01 .XXX ±.005 ANGLES ±1/2° 32</p> <p>DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS</p>	DRAWN EK	CHECKED HN	ENGINEER EK	APPROVED HN	FSCM 58167	
B	PER ECN 9765	01/29/09	JEM			DESCRIPTION PKZ, RECEPTACLE, STRAIGHT, 50 OHMS				
A	PER ECN 7063	05/02/03	HN		DATE 03/18/03	DRAWING NO. 78-1900-00			PLATING OPT. A, B, C, D	
REV.	DESCRIPTION	DATE	APPR.							