Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial Panel Connector 23_SMA-50-0-94/199_N

Description

Straight panel receptacle jack, flange mount

Interface standards SUHNER-SMA-26.5GHz



Technical Data

Electrical Data

Impedance 50 Ω Interface frequency max. 26.5 GHz

Mechanical Data

Number of matings 500
Weight 0.0029 kg

Environmental Data

Operating temperature $$-65\ ^{\circ}\text{C}$$ to 125 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PFA / PTFE	

Related Documents

Catalogue drawing DCA-00011332 Mounting hole DOU-00010189

Ordering Information

Single package 23_SMA-50-0-94/199_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.