

NOTES:

20-010-1004-04


Materials: SST. corrosion-resistant, Non Magnetic 303, per ASTM A484 and A582. Beryllium Copper per ASTM-B-196, QQ-C-530 PTFE Fluorocarbon per ASTM-D-1710


Finish: Center Conductors and solder components shall be plated per MIL-G-45204 Type II, Class 1 over Nickel plate per QQ-N-290.

Frequency: DC-27.5GHz

VSWR:  $1.05 + .005 \times \text{Frequency}$

Insertion Loss:  $.05 \sqrt{\text{Frequency}}$



LTR	DESCRIPTION	DATE	APPR.	DRAWN LMW	CHECKED	USED ON	 SRI CONNECTOR GAGE CO. 751 NORTH DRIVE MELBOURNE FL. 32934			
-	REL	11/02		APPR.	SCALE	20-010-1004-04	TITLE SMA PLUG TO .141 LL S/R			
				UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS 2. BREAK ALL CORNERS & EDGES .005 R. MAX 3. CHAMFER 1st & LAST THREADS 45° 4. SURFACE FINISHED 32/ UNLESS OTHERWISE SPECIFIED. 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN .002 T.I.R. 6. ALL DIMENSIONS ARE AFTER PLATING.		MATERIAL				
				DIMENSIONS ARE IN INCHES TOLERANCES		FINISH				
				DECIMALS      FRACTIONAL      ANGULAR .X            ±.030 .XX          ±.010            ± 1/64      .X°    ±1°0' .XXX        +.005            .X°X'   ±15'	SIZE	FSCM NO.	SHEET	DWG. NO.		
					A	OHMO1	1	20-010-1004-04		