


SMA3300-0141	SMA Plug Solder	50Ω
	_	



Parts	Material	Plating (Micro-inch)
Contact Pin	Brass	Gold 20 Over Nickel 50 Over Copper 50
Renber Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicon	
Insulator	Teflon	
Body	Brass	Gold 5 Over Nickel 50 Over Copper 50
Coupling Nut	Brass	Gold 5 Over Nickel 50 Over Copper 50

Weight: 2.36 g

Suitable Cables: Semi-rigid.141

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



## CABLE ASSEMBLY INSTRUCTION SMA3300-0141 JYE BAO CO., LTD. С BODY INSULATOR **CONTACT PIN** DIAGRAM ASSEMBLY INSTRUCTION 2.5 [.098] Step 1: STRIP AS SHOWN. Step 2: INSERT CABLE'S CENTER CONDUCTOR INTO CENTER PIN AND SOLDER IN "Y", USE 0.20 MM GAGE. ST-010 Step3: PUT CABLE INTO SOLDERING FIXTURE "ST-008". AND LOCK IT. PUT CONNECTOR AS SHOWN. Step4: SCREW LOCATOR TOOL "ST-011" TO THE POSITION AS SHOWN IN "S", AND SOLDER IN "X". Step5: USE DIELECTRIC INSERTION TOOL "ST-003" TO INSERT THE TEFLON "A".

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.