

Coaxial Cable Connector 16_SMA-50-2-103/111_N

Description

Right angle cable plug

Interface standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

| | |
|--------------------------|--------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | soldered |
| Weight | 0.0044 kg |

Environmental Data

| | |
|---|-------------------------------|
| Operating temperature 2011/65/EU, RoHS | -65 °C to 165 °C compliant |
|---|-------------------------------|

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Body | Brass | Gold Plating (Nickel underplated) |
| Insulator | PFA / PTFE | |
| Coupling nut | Bronze | Gold Plating (Nickel underplated) |
| Gasket | VMQ (Silicone rubber) | |

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00007494 |
| Catalogue drawing | DOU-00005978 |
| Assembly instruction | DOC-0000179177 |

Ordering Information

| | |
|----------------------|------------------------|
| Bulk 100 pcs package | 16_SMA-50-2-103/111_NH |
| Single package | 16_SMA-50-2-103/111_NE |

Additional Information

| | |
|-----------------|---|
| Suitable cables | EZ_86_TP_M17, SUCOFORM_86_FEP, MULTIFLEX_86 |
|-----------------|---|