

Coaxial Cable Connector 11_SMA-50-3-8/111_N

Description

Straight cable plug

Interface standards

IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0062 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU, RoHS compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Coupling nut	Bronze	Gold Plating (Nickel underplated)
Gasket	VMQ (Silicone rubber)	
Washer	PFA / PTFE	

Related Documents

Catalogue drawing DOU-00006096
Assembly instruction DOC-0000179080

Ordering Information

Bulk 100 pcs package 11_SMA-50-3-8/111_NH

Additional Information

Suitable cables RG_223_/U, ENVIROFLEX_142, RG_142_B/U, RG_400_/U