

## Coaxial Cable Connector 11\_SMA-50-2-55/199\_N

### Description

Straight cable plug

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

|                          |             |
|--------------------------|-------------|
| Impedance                | 50 $\Omega$ |
| Interface frequency max. | 18 GHz      |

#### Mechanical Data

|                |           |
|----------------|-----------|
| Centre contact | soldered  |
| Outer contact  | crimped   |
| Weight         | 0.0032 kg |

#### Environmental Data

|                       |                  |
|-----------------------|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU, RoHS      | compliant        |

#### Material Data

| Piece Parts    | Material               | Surface Plating                   |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact  | Stainless Steel        |                                   |
| Body           | Stainless Steel        |                                   |
| Insulator      | PFA / PTFE             |                                   |
| Coupling nut   | Stainless Steel        |                                   |
| Gasket         | VMQ (Silicone rubber)  |                                   |
| Crimp ferrule  | Copper                 | SUCOPLATE (R) Plating             |

### Related Documents

|                      |                |
|----------------------|----------------|
| Catalogue drawing    | DOU-00006102   |
| Assembly instruction | DOC-0000179078 |

### Ordering Information

|                |                       |
|----------------|-----------------------|
| Single package | 11_SMA-50-2-55/199_NE |
|----------------|-----------------------|

### Additional Information

|                 |  |
|-----------------|--|
| Suitable cables | RG_316_/U, ENVIROFLEX_316, RG_188_A/U, RG_174_/U |
|-----------------|--|