



NOTES: CONFORMS TO MIL-C-39012 SMC SERIES.

MATERIAL:

1. INSULATORS = TEFLON VIRGIN WHITE PER ASTM-D-1710.
2. CONTACT = BERYLLIUM COPPER PER QQ-C-530.
3. ALL OTHER METAL PARTS = BRASS 1/2 HARD PER QQ-B-626.

FINISHES:

1. CONTACT = GOLD PLATE PER MIL-G-45204 TYPE II, CLASS I, GRADE C OVER COPPER STRIKE PER MIL-C-14550.
2. ALL OTHER METAL PARTS = GOLD PLATE PER MIL-G-45204 TYPE II, CLASS 0, GRADE C OVER COPPER STRIKE PER MIL-C-14550.

PROPRIETARY INFORMATION
NOT TO BE RELEASED
WITHOUT WRITTEN PERMISSION
FROM AN AUTHORIZED
REPRESENTATIVE OF
APPLIED ENGINEERING PRODUCTS.

RIGHT ANGLE SCREW-ON FEMALE
FOR SEMI-RIGID CABLE
FOR USE WITH .085 DIA. CABLES (RG-405).

APPLIED ENGINEERING PRODUCTS
104 John W. Murphy Drive, P.O. Box 510
New Haven, CT 06513

CODE IDENT. **19505**

1005-1541-010