

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-		B	RELEASED PER ECO-12-022460	28DEC2012	RJM3	BM
			C	ECO-13-006798	26APR2013	KG	BM

1 MATERIALS:
 BODY AND CONTACT: BERYLLIUM COPPER
 PER ASTM B-196
 DIELECTRIC: TEFLON PER ASTM D-1710

2 FINISHES:
 BODY AND CONTACT: GOLD PLATE PER
 ASTM B-488

3. SMPM FEMALE INTERFACE PER
 MIL-STD-348A

4, FOR USE WITH \varnothing .047 SEMI-RIGID CABLE


5 END CAP SHIPPED UNASSEMBLED

Side view of the cable jack assembly. Dimensions shown: .202 (total length), .122 (length of the main body), \varnothing .092 (inner diameter), \varnothing .108 ± .002 (outer diameter), and \varnothing .072 ± .002 (length of the contact area).

Top view of the cable jack assembly. Dimensions shown: .150 (height), .110 (width), and \varnothing .080 (inner diameter). A callout 5 points to the end cap.

Diagram showing recommended cable strip lengths. Dimension shown: \varnothing .060 ± .008.

RECOMMENDED CABLE STRIP LENGTHS

THIS DRAWING IS A CONTROLLED DOCUMENT. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-2009		DWN B. MOYER 29JAN2007	 TE Connectivity	
DIMENSIONS: INCHES		CHK R. GROSS 29JAN2007		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD R. GROSS 29JAN2007	NAME CABLE JACK, RIGHT ANGLE, .047 SEMI-RIGID, SMPM	
0 PLC ±.1 1 PLC ±.1 2 PLC ±.02 3 PLC ±.005 4 PLC ±.0005 ANGLES ±.		PRODUCT SPEC 108-2326	RESTRICTED TO	
MATERIAL 1		APPLICATION SPEC -	SIZE A3	CAGE CODE 00779
FINISH 2		WEIGHT -	DRAWING NO C-1757643	
		CUSTOMER DRAWING	SCALE 14:1	SHEET 1 OF 1
				REV C

1470-19 (3/11)