

NOTES:

40-000-1535-00


Materials: SST. corrosion-resistant, Non Magnetic 303, per ASTM A484 and A582. Beryllium Copper per ASTM-B-196, QQ-C-530 PTFE Fluorocarbon per ASTM-D-1710 Type 1

Finish: Center Conductors and solder components shall be plated per MIL-G-45204 Type II, Class 1 over Nickel plate per QQ-N-290. Body and Body components shall be passivated per ASTM A380.

Frequency: DC-18 GHz

VSWR: 1.15 TO 18 GHz

Insertion Loss: $.05\sqrt{\text{Frequency}}$



LTR	DESCRIPTION	DATE	APPR.	DRAWN JDM	CHECKED	USED ON	SRI CONNECTOR GAGE CO. 751 NORTH DRIVE MELBOURNE FL. 32934	
-	REL	8/99		APPR.	SCALE 5X	40-000-1535-00	TITLE	
				UNLESS OTHERWISE SPECIFIED: 1. REMOVE ALL BURRS 2. BREAK ALL CORNERS & EDGES .005 R. MAX 3. CHAMFER 1st & LAST THREADS 45° 4. SURFACE ROUGHNESS 63 MIL-STD-10 5. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN T.I.R. 6. ALL DIMENSIONS ARE AFTER PLATING		MATERIAL	TNC, PLUG TO LL335 CA.	
				DIMENSIONS ARE IN INCHES TOLERANCES		FINISH		
				DECIMALS	FRACTIONAL	ANGULAR	SIZE	FSCM NO.
				.X ±.030		.X° ±1°0'	A	□HMO1
				.XX ±.015	± 1/64	.X'X' ±15'		
				.XXX ±.005				
							SHEET 1	DWG. NO. 40-000-1535-00