	ES:						40-000-1545-00
Materials: SST. corrosion-resistant, Non Magnetic 303, per ASTM A484 and A582. Beryllium Copper per ASTM-B-196, QQ-C-530 PTFE Fluorocarbon per ASTM-D-1710 Type 1							
Finish:	inish: Center Conductors and solder components shall be plated per MIL-G-45204 Type II, Class 1 over Nickel plate per QQ-N-290. Body and Body components shall be passivated per ASTM A380.						
Freque VSWR: Insertic	• • • • • • • • • •						
						(2.282)	REF
					((
LTR	DESCRIPTION	DATE	APPR.	DRAWN T MATHZ			
	REL	10/03		APPR.	SCALE	40-000-1545-00	SRI CONNECTOR GAGE CO. 751 NORTH DRIVE MELBOURNE FL. 32934
				UNLESS OTHERWISE SPECI	& EDGES .005 R. MAX THREADS 45" INLESS OTHERWISE SPECIFIED. N CENTERS TO BE D2 T.I.R.	MATERIAL TITLE FINISH I	TNC PLUG TO LL450
				.X ±.030	RE IN INCHES ANCES TIONAL ANGULAR /64 .X° ±1°0' .X°X' ±15'	SIZE FSCM NO. SHEET A OHMO1 1	dwg. no. 40-000-1545-00