Data Sheet



Coaxial PCB Connector 83_CT-0-2-4/-11_N-1

Description

Straight PCB cable terminator

Interface Standards



Technical Data

Electrical Data

Impedance other Ω

Mechanical Data

Board mounting type through holes Weight 0.0003 kg

Environmental Data

Operating temperature $$-65\,^{\circ}\text{C}$$ to 165 $^{\circ}\text{C}$$ 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact		
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating

Related Documents

 Outline drawing
 DOU-00012733

 Catalogue drawing
 DCA-00012735

 Assembly instruction
 DOC-0000192786

 Mounting hole
 DOU-00012682

Ordering Information

 Single package
 83_CT-0-2-4/-11_NE-1

 Bulk 100 pcs package
 83_CT-0-2-4/-11_NH-1

Remarks

PCB connector without stand-offs, cable group Y3, Y11, Y16 (EZ_86), cable entry: soldered

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

06.11.2017