

RF Attenuator 6806_QMA-50-2/133_N

Description

Standard Attenuator, Low Power



Product Configuration

Connector (side 1 / side 2) QMA plug (male) / QMA jack (female)
 Interface Standards QMA QLF compliant

Technical Data

Electrical Data

Nominal impedance 50 Ω
 Nominal attenuation 6 dB
 Frequency range DC to 6 GHz
 Attenuation deviation (±dB) 0.6
 VSWR max. 1.2
 Power rating 2 Watt average power up to 25 °C ambient temperature, linearly derated to 0.5 Watt at 125 °C ambient temperature.

Mechanical Data

Weight 0.009 kg

Environmental Data

Operating temperature -40 °C to 85 °C
 2011/65/EU (RoHS) compliant

Material Data

Piece Part (side 1)	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Bronze	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Piece Part (side2)	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	

Related Documents

Outline drawing DOU-00100355

Ordering Information

Single packaging 6806_QMA-50-2/133_NE